

Okehampton Business Park Exeter Road Okehampton Devon EX20 1UB Telephone 01837 54446/7 Fax 01837 54544

Certificate of Analysis Part No. B2923 Lube Oil Standard

Certificate Number 933213 Page 1 of 1

Weight Percent Sulphur = 0.0805 Expanded Uncertainty = 0.002 (k=2, 95% confidence limit)

Method used for analysis: ASTM D 4294-10 NMI Standard(s) used: NIST SRM 1819a I, II, III

This standard was produced gravimetrically using high purity materials, with balances calibrated and checked by precision NIST traceable weights. The above ASTM test method and NMI references listed were used for testing. The uncertainty value represents the 95% confidence limit (k=2) derived from analysis (n=50), and possible errors in weighing. When necessary, professional judgment is applied toward consideration of data and statistical information. Normal test procedures should be employed when using this standard. This includes using the *reproducibility* and *repeatability* factors for the test method you wish to employ. The material used in production of this standard was sampled in accordance with ARI 032. The samples for round robin testing were selected in accordance with ARI 014. The above values relate only to the material used to produce this standard.

Notes:

Before use, the contents of the bottle should be mixed by vigorous shaking. Any exposure to air and light should be kept to a minimum. Keep sealed and store upright under normal laboratory conditions. This bottle contains 100ml to be used as per the test method. Unopened and stored properly this product has an indefinite shelf life. Once opened this standard is only valid for two years.

This Reference Material (Working Standard) is traceable to the above-mentioned NMI standards. For good laboratory practice it is recommended that all standards be verified prior to use. Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Elemental Microanalysis Ltd be liable for incidental or consequential damages.

EXPIRATION DATE: THIS REFERENCE MATERIAL IS VALID FOR TWO YEARS FROM THE DATE OF OPENING

Certified March 12, 2013

Elemental Microanalysis Limited