



Okehampton Business Park
Exeter Road
Okehampton
Devon EX20 1UB
Telephone 01837 54446/7
Fax 01837 54544

Certificate of Analysis
Part No. B2939
Sulphur & Chlorine Lube Oil
Standard

Certificate Number 502516
Page 1 of 1

WEIGHT % SULFUR = 5.00
STANDARD DEVIATION = 0.25
WEIGHT % CHLORINE = 2.00
STANDARD DEVIATION = 0.10

This standard was produced gravimetrically using high purity materials with balances calibrated and checked by precision NIST traceable weights. The precision value represents the expanded degree of uncertainty based on errors from assay and weighing of raw materials at a 95% confidence level ($k=2$). When necessary, professional judgment is applied toward consideration of data and statistical information. Normal ASTM procedures should be employed when using this standard. This includes using the *reproducibility* and *repeatability* factors for the test method you wish to employ.

Before use, the contents of the bottle should be mixed through vigorous shaking. The contents should not be exposed to air for a lengthy period. This bottle contains 100ml prepared mineral oil to be used as per your test method. Kept sealed this reference has an indefinite shelf life, once opened this certificate is valid for 2 years.

This is a prepared Reference Material (RM), for good laboratory practice it is recommended that all standards be verified prior to use. Remedies for any claimed defect in this product will be limited to product replacement or refund of the purchase price. In no event shall Elemental Microanalysis Ltd be liable for incidental or consequential damages.

EXPIRATION DATE:
THIS RM IS VALID FOR TWO YEARS FROM THE DATE OF OPENING

Certified May 4, 2016

Elemental Microanalysis Limited